



USA WORKING EQUITATION



Obstacle Specifications

| | |
|---|---|
| No. of obstacles required | L1–L3: 10. L4 & L5: 13. L6 & L7: 15. |
| Distance btw consecutive obstacles and entry/exit | 10 m (30 ft) min. (line of travel) |
| Distance from public | 5 m (15 ft) min. |
| Entrance/exit markers | 1.5 m (5 ft) min; 3 m (10 ft) max. |
| 1. Bridge | Entry/exit markers are required. |
| 2. Figure 8 | Distance between drums: 3-m (10-ft) on center. |
| 3. Pen | Outer pen: 6 m (20 ft) in dia. Inner pen 3 m (10 ft) in dia. Entrance: 1.5 to 2.5 m (5- to 8-ft). Corridor: 1.5 m (5-ft). |
| 4. Jug | Table: 1.2 m (4 ft). Jug must be in same position for all competitors. Must be accessible from either side. Entry/exit markers are required. |
| 5. Remove Pole | Pole: 2.5 to 3.5 m (8 to 11.5 ft). Must be accessible from either side. |
| 6. Spear Ring | Ring: 15 cm (6 in.) in dia. (approx.). Must be accessible from either side. |
| 7. Replace Pole | Must be accessible from either side. |
| 8. Switch Cup | Bending poles: 2 m (6.5 ft) high (approx.). Distance: 1.2 m (4 ft) apart. Cup: must be set on same pole for all riders <i>unless WAWE rules are used</i> . |
| 9. Bell Corridor | Rails: 30 cm (12 in.) high; 3.7 m (12 ft.) long; 1.5 m (5 ft.) apart. Bell: 2 m (6.5 ft) high; positioned in center of corridor. |
| 10. Reinback “L” | Rails: 30 cm (12 in.) high (min); 3.7 m (12 ft) long. “L” in either direction. Corridor width: 1.5 m (5 ft). |
| 11. Rounding Posts | Corridor width: 1.5 m (5 ft). Distance btw posts: 2.5 m (8 ft) min; 3 m (10 ft) max. |
| 12. Single Slalom | Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Entry/exit markers are recommended. |
| 13. Double Slalom | Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Corridor width: 6 m (20 ft). L1-L5: Five posts; L6 & L7: seven posts. Entry/exit markers are recommended. |
| 14. Gate | Height: 1.3 m (4 ft 3 in.) min. Width: 2 m (6.5 ft) min. |
| 15. Jump | Width: 3 m (10 ft) min. L1: cross-rail no higher than 0.3 m (12 in.) at center. L2/L3: Crossed rails 0.5 m (22 in.) at standard; 0.4 m (15 in.) at center. L4–L7: 0.5 m (22 in.) high. Must have a ground pole. |
| 16. Sidepass Rail | Rail: 10 cm (4 in.) dia.; 3.7 m (12 ft) long; 5-10 cm (2-4 in) above ground. Two rails in line or parallel rails: 3 m (10 ft) apart Entry/exit markers are required. |
| 17. Water | Minimum 1.5 m (5 ft) long; 2.4 m (8 ft) wide; 10 cm (4 in.) deep; maximum depth 20 cm (8 in.) |
| 18. Bank | 30-60 cm (1-2 ft) above ground level. Plateau 2 m (6.5 ft) long. |
| 19. Drums | L1–L5: 4 m (13 ft); L6 & L7: 3 m (10 ft) |