

No. of obstacles required <i>(minimum)</i>	L1-8	L2-L3: 10	L4 & L5: 12	L6 & L7: 15
Distance btw consecutive obstacles and entry/exit	10 m (30 ft) min. (line of travel)			
Distance from public	5 m (15 ft) min.			
Entrance/exit markers	1.5 m (5 ft) min; 3 m (10 ft) max.			
1. Bridge	Entry/exit markers are required.			
2. Figure 8	Distance between drums: 3-m (10-ft) on center.			
3. Pen	Outer pen: 6 m (20 ft) in dia. Inner pen 3 m (10 ft) in dia. Entrance: 1.5 to 2.5 m (5- to 8-ft). Corridor: 1.5 m (5-ft).			
4. Jug	Table: 1.2 m (4 ft). Jug must be in same position for all competitors. Must be accessible from either side. Entry/exit markers are required.			
5. Remove Pole	Pole: 2.5 to 3.5 m (8 to 11.5 ft). Must be accessible from either side.			
6. Spear Ring	Ring: 15 cm (6 in.) in dia. (approx.). Must be accessible from either side.			
7. Replace Pole	Must be accessible from either side.			
8. Switch Cup	Bending poles: 2 m (6.5 ft) high (approx.). Distance: 1.2 m (4 ft) apart. Cup: must be set on same pole for all riders <i>unless WAVE rules are used</i> .			
9. Bell Corridor	Rails: 30 cm (12 in.) high; 3.7 m (12 ft.) long; 1.5 m (5 ft.) apart. Bell: 2 m (6.5 ft) high; positioned in center of corridor.			
10. Reinback "L"	Rails: 30 cm (12 in.) high (min); 3.7 m (12 ft) long. "L" in either direction. Corridor width: 1.5 m (5 ft).			
11. Rounding Posts	Corridor width: 1.5 m (5 ft). Distance btw posts: 2.5 m (8 ft) min; 3 m (10 ft) max.			
12. Single Slalom	Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Entry/exit markers are recommended.			
13. Double Slalom	Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Corridor width: 6 m (20 ft). L1-L5: Five posts; L6 & L7: seven posts. Entry/exit markers are recommended.			
14. Gate	Height: 1.3 m (4 ft 3 in.) min. Width: 2 m (6.5 ft) min.			
15. Jump	Width: 3 m (10 ft) min. L1: cross-rail no higher than 0.3 m (12 in.) at center. L2/L3: Crossed rails 0.5 m (22 in.) at standard; 0.4 m (15 in.) at center. L4-L7: 0.5 m (22 in.) high. Must have a ground pole.			
16. Sidepass Rail	Rail: 10 cm (4 in.) dia.; 3.7 m (12 ft) long; 5-10 cm (2-4 in) above ground. Two rails in line or parallel rails: 3 m (10 ft) apart Entry/exit markers are required.			
17. Water	Minimum 1.5 m (5 ft) long; 2.4 m (8 ft) wide; 10 cm (4 in.) deep; maximum depth 20 cm (8 in.)			
18. Bank	30-60 cm (1-2 ft) above ground level. Plateau 2 m (6.5 ft) long.			
19. Drums	L1-L5: 4 m (13 ft); L6 & L7: 3 m (10 ft)			