

No. of obstacles required (min)	L1–8	L2-L3: 10	L4 & L5: 12	L6 & L7: 15
Distance btw consecutive obstacles and entry/exit	10 m (30 ft) min. (line of travel)			
Distance from public	5 m (15 ft) min.			
Entrance/exit markers	1.5 m (5 ft) min; 3 m (10 ft) max.			
1. Bridge	Entry/exit markers are required.			
2. Figure 8	Distance between drums: 3 m (10 ft) on center.			
3. Pen	Outer pen: 6 m (20 ft) in dia. Inner pen 3 m (10 ft) in dia. Entrance: 1.5 to 2.5 m (5 to 8 ft). Corridor: 1.5 m (5 ft). The pen must fall down if hit by horse or competitor.			
4. Jug	Table height: 1.2 m (4 ft). Jug must have a handle and be in the same position for all competitors. Must be accessible from either side. Entry/exit markers are required.			
5. Remove Pole	Pole: 2.5 to 3.5 m (8 to 11.5 ft). Must be accessible from either side and have an easily identifiable tip.			
6. Spear Ring	Ring: Approx. 15 cm (6 in.) in dia., made of wood, metal, or plastic. Must be accessible from either side.			
7. Replace Pole	Must be accessible from either side.			
8. Switch Cup	Bending poles: 1.5-2 m (5-6.5 ft) high (approx.). Distance: 1.2 m (4 ft) apart. Cup: must be set on same pole for all riders <i>unless WAVE rules are used</i> .			
9. Bell Corridor	Rails: 30 cm (12 in.) high; 3.7 m (12 ft.) long; 1.5 m (5 ft.) apart. Bell: Two bells 1.5-1.8m (5-6 ft) high, one on each side, at end of corridor or one bell, 2 m (6.5ft) high, positioned at end of corridor.			
10. Reinback "L"	Rails: 30 cm (12 in.) high (min); 3.7 m (12 ft) long. "L" in either direction. Corridor width: 1.5 m (5 ft).			
11. Rounding Posts	Corridor width: 1.5 m (5 ft). Distance btw posts: 2.5 m (8 ft) min; 3 m (10 ft) max.			
12. Single Slalom	Posts: 2 m (6.5 ft) high. Plants or other objects at least .61 m (2 ft) in height may be used instead of poles. Distance btw posts: 7 m (23 ft) for L1-L5. Distance btw posts: 6m (20 ft) for L6 & L7 . Entry/exit markers are recommended.			
13. Double Slalom	Posts: 2 m (6.5 ft) high. Plants or other objects at least .61 m (2 ft) in height may be used instead of poles. L1-L5: Five posts. Distance btw posts: 7 m (23 ft) L6 & L7: Seven posts. Distance btw posts: 6m (20 ft). Entry/exit markers are recommended.			
14. Gate	Recommended height of the gate is 1.5 m (5 ft) tall and 2.1 m (7 ft) wide. The gate must be at least 1.3 m (4 ft 3 in.) high, and 2 m (6.5 ft) wide.			
15. Jump	Width: at least 2.5 m - 3.5 m (8 ft-12 ft) L1: cross-rail no higher than 0.3 m (12 in.) at center. L2/L3: Crossed rails 0.5 m (22 in.) at standard; 0.4 m (15 in.) at center. L4–L7: 0.5 m (22 in.) high. Must have a ground pole.			
16. Sidepass Rail	Rail: 10 cm (4 in.) dia.; 3 m - 3.5 m (10 ft-12 ft) long ; 5-10 cm (2 in-4 in) above ground. Two rails in line or parallel rails: 3 m (10 ft) apart; two rails in "L" configuration. Entry/exit markers are required.			
17. Water	Minimum 1.5 m (5 ft) long; 2.4 m (8 ft) wide; 10 cm (4 in.) deep; maximum depth 20 cm (8 in.)			
18. Bank	Vertical change not more than 30 cm to 60 cm (1 ft to 2 ft) above/below ground level; at least 12 ft (one stride or more) in the direction of travel between the up and down elements; face should be at least 8 ft wide. When only one direction is required, there will be a ramp or incline of at least 8 ft on the other side.			
19. Drums	L1–L5: 4 m (13 ft); L6 & L7: 3 m (10 ft)			